

SHELL ROTELLA® T3 FLEET 15W-40

Heavy Duty Diesel Engine Oil

Shell ROTELLA® T3 Fleet heavy duty engine oil has been formulated to provide reliable protection and performance in fleet and off-highway equipment, offering the convenience of a single oil suitable for a wide range of OEMs.

Shell ROTELLA® T3 Fleet has been designed to provide hard working protection that adapts to your driving conditions resulting in:

- Improved deposit protection versus prior formulation
- Demonstrated resistance to breakdown under high temperatures
- Demonstrated protection against oxidation and corrosion in the presence of biodiesel

The low ash formulation helps protect the exhaust catalysts and particulate filters found on the latest low emission vehicles.

	Rotella T3 (CJ-4)	Rotella T3 Fleet (CK-4)
Cleanliness/Deposits Protection	& & &	& & & &
Wear Protection		
Oxidation Control	& &	6666
Bio-Fuel Compatibility	& &

The Engine Oil That Works As Hard As You. The Works As You. The Engine Oil That Works As You. The Works As You. T

Checkmarks indicate relative performance of prior CJ-4 formulation compared to CK-4 formulation

PERFORMANCE, FEATURES & BENEFITS

Helps control engine wear

Shell ROTELLA® T3 Fleet has been formulated to help protect against wear, and has been tested and proven through field trials and industry wear tests to maximize engine efficiency and help prolong engine life.

Helps control deposits in engines

Formulated for enhanced deposit protection, which exceeds API CK-4 deposit test requirements, to help keep engines cleaner over the oil drain interval.

Improved oxidation protection under extreme conditions

Shell ROTELLA® T3 Fleet delivers improved resistance to oil breakdown under extreme high temperature conditions versus prior CJ-4 performance specification.

Extended drain capable

Proven performance in standard oil drain intervals up to 50,000 km and tested in field trials to show Shell ROTELLA® T3 Fleet demonstrates good TBN retention, low TAN increase, low wear metals, and low oxidation at drain. Always follow OEM recommendations when it comes to setting drain intervals for your specific operations and equipment.



MAIN APPLICATIONS

Suitable for use in all on or off highway engines requiring an API CK-4, CJ-4, Cl-4 Plus, Cl-4 or CH-4 diesel oil in this viscosity grade.













Provides reliable protection in fleet and off-highway equipment including the latest emission controlled engines using EGR and containing a Diesel Particulate Filter.

Off-highway applications

Suitable for use in agricultural, mining, logging, and construction applications, even with high levels of fuel sulfur.

Our complementary range

In addition to a full range of Shell ROTELLA® Heavy Duty Engine Oils, Shell Lubricants offers a complete portfolio of lubricants for every part of your equipment, including Shell SPIRAX® gear/axle oils and transmission fluids, Shell GADUS® greases, and Shell Antifreeze/Coolants.



OEM SPECIFICATIONS AND APPROVALS

SAE 15W-40 API and OEM Approvals

API CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4

ACEA E9; JASO DH-2; Cummins 20086; Volvo VDS-4.5; DDC DFS 93K222; Caterpillar ECF-2, ECF-3; MB-Approval 228.31; MAN M3575; MTU Category Type 2.1; Deutz DQC-III 10 LA; Allison TES 439; MACK EOS-4.5; Ford WSS-M2C171-F1

PRODUCT MATERIAL CODE & PACKAGE SIZE

PRODUCT	5 Gal Pail	55 Gal Drum	Bulk
T3 Fleet 15W-40	550046220	550046212	500010131

For more information, contact your local **Shell Lubricants Representative or visit** www.shell.ca/rotella

The term 'Shell Lubricants' collectively refers to individual Shell Group companies engaged in the lubricants business throughout the world. These are separate and distinct entities. The collective expressions 'Shell' and 'Shell Lubricants' may be used herein for convenience where reference is made in general to those companies or where no useful purpose is served by identifying any particular company or companies.

